

Package: DiceView (via r-universe)

October 4, 2026

Title Methods for Visualization of Computer Experiments Design and Surrogate

Version 4.0

Date 2026-06-17

Maintainer Yann Richet <yann.richet@asn.fr>

Description View 2D/3D sections, contour plots, mesh of excursion sets for computer experiments designs, surrogates or test functions.

Depends methods, utils, stats, grDevices, graphics

Imports DiceDesign, R.cache, geometry, scatterplot3d, parallel, foreach

Suggests rlikkriging, DiceKriging, DiceEval, rgl, arrangements, parallelPlot

License GPL-3

URL <https://github.com/IRSN/DiceView>

Encoding UTF-8

Config/roxygen2/version 8.0.0

Repository <https://irsn.r-universe.dev>

Date/Publication 2026-09-04 19:38:05 UTC

RemoteUrl <https://github.com/irsn/diceview>

RemoteRef HEAD

RemoteSha 1d44405bf692b8add6ff9460f7e6332142bbffd5

Contents

Apply.function	2
are_in.mesh	3
branin	4
combn.design	4
contourview.function	5
EvalInterval.function	13

expand.grids	13
filledcontourview.function	14
is.mesh	21
is_in.mesh	22
is_in.p	22
load3d	23
Memoize.function	23
mesh	24
mesh_exsets	25
mesh_level	26
min_dist	27
min_dist.mesh	27
optim.stop	28
optims	29
parview.function	30
plot_mesh	34
plot2d_mesh	35
plot3d_mesh	36
points_in.mesh	37
points_out.mesh	38
root	38
roots	40
roots_mesh	41
safe_mclapply	43
sectionview.function	43
sectionview3d.function	51
Vectorize.function	59
Index	60

Apply.function	<i>Apply Functions Over Array Margins, using custom vectorization (possibly using parallel)</i>
----------------	---

Description

Emulate parallel apply on a function, from mclapply. Returns a vector or array or list of values obtained by applying a function to margins of an array or matrix.

Usage

```
Apply.function(FUN, X, MARGIN = 1, .combine = c, .lapply = safe_mclapply, ...)
```

Arguments

<code>FUN</code>	function to apply on <code>X</code>
<code>X</code>	array of input values for <code>FUN</code>
<code>MARGIN</code>	1 indicates to apply on rows (default), 2 on columns
<code>.combine</code>	how to combine results (default using <code>c(.)</code>)
<code>.lapply</code>	how to vectorize <code>FUN</code> call (default is <code>parallel::mclapply</code>)
<code>...</code>	optional arguments to <code>FUN</code> .

Value

array of values taken by `FUN` on each row/column of `X`

Examples

```
X = matrix(runif(10),ncol=2);
rowSums(X) == apply(X,1,sum)
apply(X,1,sum) == Apply.function(sum,X)

X = matrix(runif(10),ncol=1)
rowSums(X) == apply(X,1,sum)
apply(X,1,sum) == Apply.function(sum,X)

X = matrix(runif(10),ncol=2)
f = function(X) X[1]/X[2]
apply(X,1,f) == Apply.function(f,X)
```

are_in.mesh

Checks if some points belong to a given mesh

Description

Checks if some points belong to a given mesh

Usage

```
are_in.mesh(X, mesh)
```

Arguments

<code>X</code>	points to check
<code>mesh</code>	mesh identifying the set which <code>X</code> may belong

Examples

```
X = matrix(runif(100),ncol=2);
inside = are_in.mesh(X,mesh=geometry::delanayn(matrix(c(0,0,1,1,0,0),ncol=2),output.options =TRUE))
print(inside)
plot(X,col=rgb(1-inside,0,0+inside))
```

branin	<i>This is a simple copy of the Branin-Hoo 2-dimensional test function, as provided in DiceKriging package. The Branin-Hoo function is defined here over $[0,1] \times [0,1]$, instead of $[-5,0] \times [10,15]$ as usual. It has 3 global minima : $x1 = c(0.9616520, 0.15)$; $x2 = c(0.1238946, 0.8166644)$; $x3 = c(0.5427730, 0.15)$</i>
--------	--

Description

This is a simple copy of the Branin-Hoo 2-dimensional test function, as provided in DiceKriging package. The Branin-Hoo function is defined here over $[0,1] \times [0,1]$, instead of $[-5,0] \times [10,15]$ as usual. It has 3 global minima : $x1 = c(0.9616520, 0.15)$; $x2 = c(0.1238946, 0.8166644)$; $x3 = c(0.5427730, 0.15)$

Usage

```
branin(x)
```

Arguments

x	a 2-dimensional vector specifying the location where the function is to be evaluated.
---	---

Value

A real number equal to the Branin-Hoo function values at x

combn.design	<i>Generalize expand.grid() for multi-columns data. Build all combinations of lines from X1 and X2. Each line may hold multiple columns.</i>
--------------	--

Description

Generalize expand.grid() for multi-columns data. Build all combinations of lines from X1 and X2. Each line may hold multiple columns.

Usage

```
combn.design(X1, X2)
```

Arguments

X1	variable values, possibly with many columns
X2	variable values, possibly with many columns combn.design(matrix(c(10,20),ncol=1),matrix(c(1,2,3,4,5,6),ncol=2)) combn.design(matrix(c(10,20,30,40),ncol=2),matrix(c(1,2,3,4,5,6),ncol=2))

contourview.function	<i>Plot a contour view of a prediction model or function, including design points if available.</i>
----------------------	---

Description

Plot a contour view of a prediction model or function, including design points if available.

Usage

```
## S3 method for class '`function`'
contourview(
  fun,
  vectorized = FALSE,
  center = NULL,
  lty_center = 2,
  col_center = "black",
  axis = NULL,
  npoints = 21,
  levels = 10,
  lty_levels = 3,
  col_levels = if (!is.null(col) & length(col) == 1) col.levels(col, levels - 1) else if
    (!is.null(col) & length(col) == 2) cols.levels(col[1], col[2], levels - 1) else
    col.levels("blue", levels - 1),
  col = NULL,
  col_fading_interval = 0.5,
  mfrow = NULL,
  Xlab = NULL,
  ylab = NULL,
  Xlim = if (!add) matrix(c(0, 1), 2, 2) else NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  ...
)

## S3 method for class 'matrix'
contourview(
  X,
  y,
  center = NULL,
  lty_center = 2,
  col_center = "black",
  axis = NULL,
  col_points = if (!is.null(col)) col else "red",
  col = NULL,
```

```

    bg_fading = 1,
    mfrow = NULL,
    Xlab = NULL,
    ylab = NULL,
    Xlim = if (!add) matrix(c(0, 1), 2, 2) else NULL,
    ylim = NULL,
    title = NULL,
    title_sep = " | ",
    add = FALSE,
    ...
)

## S3 method for class 'character'
contourview(eval_str, axis = NULL, mfrow = NULL, ...)

## S3 method for class 'km'
contourview(
  km_model,
  type = "UK",
  center = NULL,
  axis = NULL,
  npoints = 21,
  levels = pretty(km_model@y, 10),
  col_points = if (!is.null(col) & length(col) == 1) col else "red",
  col_levels = if (!is.null(col) & length(col) == 1) col.levels(col, levels) else if
    (!is.null(col) & length(col) == 2) cols.levels(col[1], col[2], levels - 1) else
    col.levels("blue", levels),
  col = NULL,
  conf_level = 0.5,
  conf_fading = 0.5,
  bg_fading = 1,
  mfrow = NULL,
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  ...
)

## S3 method for class 'Kriging'
contourview(
  Kriging_model,
  center = NULL,
  axis = NULL,
  npoints = 21,

```

```

    levels = pretty(Kriging_model$y(), 10),
    col_points = if (!is.null(col) & length(col) == 1) col else "red",
    col_levels = if (!is.null(col) & length(col) == 1) col.levels(col, levels) else if
      (!is.null(col) & length(col) == 2) cols.levels(col[1], col[2], levels - 1) else
      col.levels("blue", levels),
    col = NULL,
    conf_level = 0.5,
    conf_fading = 0.5,
    bg_fading = 1,
    mfrow = NULL,
    Xlab = NULL,
    ylab = NULL,
    Xlim = NULL,
    ylim = NULL,
    title = NULL,
    title_sep = " | ",
    add = FALSE,
    ...
  )

```

```
## S3 method for class 'WarpKriging'
```

```

contourview(
  WarpKriging_model,
  center = NULL,
  axis = NULL,
  npoints = 21,
  levels = pretty(WarpKriging_model$y(), 10),
  col_points = if (!is.null(col) & length(col) == 1) col else "red",
  col_levels = if (!is.null(col) & length(col) == 1) col.levels(col, levels) else if
    (!is.null(col) & length(col) == 2) cols.levels(col[1], col[2], levels - 1) else
    col.levels("blue", levels),
  col = NULL,
  conf_level = 0.5,
  conf_fading = 0.5,
  bg_fading = 1,
  mfrow = NULL,
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  ...
)

```

```
## S3 method for class 'glm'
```

```

contourview(

```

```

    glm_model,
    center = NULL,
    axis = NULL,
    npoints = 21,
    levels = pretty(glm_model$fitted.values, 10),
    col_points = if (!is.null(col) & length(col) == 1) col else "red",
    col_levels = if (!is.null(col) & length(col) == 1) col.levels(col, levels) else if
      (!is.null(col) & length(col) == 2) cols.levels(col[1], col[2], levels - 1) else
      col.levels("blue", levels),
    col = NULL,
    conf_level = 0.5,
    conf_fading = 0.5,
    bg_fading = 1,
    mfrow = NULL,
    Xlab = NULL,
    ylab = NULL,
    Xlim = NULL,
    ylim = NULL,
    title = NULL,
    title_sep = " | ",
    add = FALSE,
    ...
  )

## S3 method for class 'list'
contourview(
  modelFit_model,
  center = NULL,
  axis = NULL,
  npoints = 21,
  levels = pretty(modelFit_model$data$Y, 10),
  col_points = if (!is.null(col) & length(col) == 1) col else "red",
  col_levels = if (!is.null(col) & length(col) == 1) col.levels(col, levels) else if
    (!is.null(col) & length(col) == 2) cols.levels(col[1], col[2], levels - 1) else
    col.levels("blue", levels),
  col = NULL,
  bg_fading = 1,
  mfrow = NULL,
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  ...
)

```

```
contourview(...)
```

Arguments

fun	a function or 'predict()'-like function that returns a simple numeric or mean and standard error: list(mean=...,se=...).
vectorized	is fun vectorized?
center	optional coordinates (as a list or data frame) of the center of the section view if the model's dimension is > 2.
lty_center	line type for the section center of the plot (if any).
col_center	color for the section center of the plot (if any).
axis	optional matrix of 2-axis combinations to plot, one by row. The value NULL leads to all possible combinations i.e. choose(D, 2).
npoints	an optional number of points to discretize plot of response surface and uncertainties.
levels	(number of) contour levels to display.
lty_levels	contour line type.
col_levels	color for the surface.
col	color of the object (use col_* for specific objects).
col_fading_interval	an optional factor of alpha (color channel) fading used to plot function output intervals (if any).
mfrow	an optional list to force par(mfrow = ...) call. The default value NULL is automatically set for compact view.
Xlab	an optional list of string to overload names for X.
ylab	an optional string to overload name for y.
Xlim	an optional list to force x range for all plots. The default value NULL is automatically set to include all design points.
ylim	an optional list to force y range for all plots.
title	an optional overload of main title.
title_sep	customize subtitle with fixed input.
add	to print graphics on an existing window.
...	arguments of the contourview.km, contourview.glm, contourview.Kriging or contourview.function function
X	the matrix of input design.
y	the array of output values (two columns means an interval).
col_points	color of points.
bg_fading	an optional factor of alpha (color channel) fading used to plot design points outside from this section.
eval_str	the expression to evaluate in each subplot.
km_model	an object of class "km".

type the kriging type to use for model prediction.
 conf_level confidence hulls to display.
 conf_fading an optional factor of alpha (color channel) fading used to plot confidence hull.
 Kriging_model an object of class "Kriging".
 WarpKriging_model an object of class "WarpKriging".
 glm_model an object of class "glm".
 modelFit_model an object returned by DiceEval::modelFit.

Details

If available, experimental points are plotted with fading colors. Points that fall in the specified section (if any) have the color specified `col_points` while points far away from the center have shaded versions of the same color. The amount of fading is determined using the Euclidean distance between the plotted point and center.

Author(s)

Yann Richet, ASNR

See Also

[sectionview.function](#) for a section plot, and [sectionview3d.function](#) for a 2D section plot.
[sectionview.matrix](#) for a section plot, and [sectionview3d.matrix](#) for a 2D section plot.
[contourview.matrix](#) for a section plot.
[sectionview.km](#) for a section plot, and [sectionview3d.km](#) for a 2D section plot.
[sectionview.Kriging](#) for a section plot, and [sectionview3d.Kriging](#) for a 2D section plot.
[sectionview.WarpKriging](#) for a section plot, and [sectionview3d.WarpKriging](#) for a 2D section plot.
[sectionview.glm](#) for a section plot, and [sectionview3d.glm](#) for a 2D section plot.

Examples

```

x1 <- rnorm(15)
x2 <- rnorm(15)

y <- x1 + x2 + rnorm(15)
model <- lm(y ~ x1 + x2)

contourview(function(x) sum(x),
             xlim=cbind(range(x1),range(x2)), col='black')
points(x1,x2)

contourview(function(x) {
  x = as.data.frame(x)
  colnames(x) <- all.vars(model$call)[-1]
  predict.lm(model, newdata=x, se.fit=FALSE)
})
```

```

    }, vectorized=TRUE, add=TRUE)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

contourview(X, y)

x1 <- rnorm(15)
x2 <- rnorm(15)

y <- x1 + x2^2 + rnorm(15)
model <- glm(y ~ x1 + I(x2^2))

contourview(model)

contourview("abline(h=0.25,col='red')")
if (requireNamespace("DiceKriging")) { library(DiceKriging)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

model <- km(design = X, response = y, covtype="matern3_2")

contourview(model)

}

if (requireNamespace("rlikkriging")) { library(rlikkriging)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

model <- Kriging(X = X, y = y, kernel="matern3_2")

contourview(model)

}

if (requireNamespace("rlikkriging")) { library(rlikkriging)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin) + 5*rnorm(15)

model <- WarpKriging(y = y, X = X, warping = c("affine","affine"), kernel="matern3_2")

contourview(model)

}

x1 <- rnorm(15)
x2 <- rnorm(15)

y <- x1 + x2^2 + rnorm(15)

```

```

model <- glm(y ~ x1 + I(x2^2))

contourview(model)

if (requireNamespace("DiceEval")) { library(DiceEval)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

model <- modelFit(X, y, type = "StepLinear")

contourview(model)

}

## A 2D example - Branin-Hoo function
contourview(branin, levels=30, col='black')

## Not run:
## a 16-points factorial design, and the corresponding response
d <- 2; n <- 16
design.fact <- expand.grid(seq(0, 1, length = 4), seq(0, 1, length = 4))
design.fact <- data.frame(design.fact); names(design.fact) <- c("x1", "x2")
y <- branin(design.fact); names(y) <- "y"

if (requireNamespace("DiceKriging")) { library(DiceKriging)
## model: km
model <- DiceKriging::km(design = design.fact, response = y)
contourview(model, levels=30)
contourview(branin, levels=30, col='red', add=TRUE)
}

if (requireNamespace("rlikkriging")) { library(rlikkriging)
## model: Kriging
model <- Kriging(X = as.matrix(design.fact), y = as.matrix(y), kernel="matern3_2")
contourview(model, levels=30)
contourview(branin, levels=30, col='red', add=TRUE)
}

## model: glm
model <- glm(y ~ 1+ x1 + x2 + I(x1^2) + I(x2^2) + x1*x2, data=cbind(y,design.fact))
contourview(model, levels=30)
contourview(branin, levels=30, col='red', add=TRUE)

if (requireNamespace("DiceEval")) { library(DiceEval)
## model: StepLinear
model <- modelFit(design.fact, y, type = "StepLinear")
contourview(model, levels=30)
contourview(branin, levels=30, col='red', add=TRUE)
}

## End(Not run)

```

EvalInterval.function *eval function and cast result to a list of y, y_low, y_up (possibly NA)*

Description

eval function and cast result to a list of y, y_low, y_up (possibly NA)

Usage

```
EvalInterval.function(fun, X, vectorized = FALSE, dim = ncol(X))
```

Arguments

fun	function to evaluate
X	matrix of input values for fun
vectorized	whether fun is vectorized or not
dim	dimension of input values for fun if

Value

list of y, y_low, y_up

expand.grids *Create a Data Frame from all combinations of factor variables*

Description

Generalization of base::expand.grid to more than 2 variables.

Usage

```
expand.grids(d = length(list(...)), ...)
```

Arguments

d	number of variables (taken in following arguments with modulo)
...	variables to combine, as arrays of values

Value

data frame of all possible combinations of variables values

Examples

```
expand.grids(d=1)
expand.grids(d=1,seq(f=0,t=1,l=11))
expand.grids(d=2)
expand.grids(d=2,seq(f=0,t=1,l=11))
expand.grids(d=2,seq(f=0,t=1,l=11),seq(0,1,l=3))
expand.grids(d=3,seq(f=0,t=1,l=5))
expand.grids(d=NULL,seq(f=0,t=1,l=5),seq(f=0,t=1,l=5),seq(f=0,t=1,l=5))
expand.grids(seq(f=0,t=1,l=5),seq(f=0,t=1,l=5),seq(f=0,t=1,l=5))
expand.grids(d=4,seq(f=0,t=1,l=5))
```

filledcontourview.function

Plot a contour view of a prediction model or function, including design points if available.

Description

Plot a contour view of a prediction model or function, including design points if available.

Usage

```
## S3 method for class ``function``
filledcontourview(
  fun,
  vectorized = FALSE,
  center = NULL,
  lty_center = 2,
  col_center = "black",
  axis = NULL,
  npoints = 21,
  levels = 10,
  lty_levels = 0,
  col_levels = if (!is.null(col) & length(col) == 1) col.levels(col, levels, fill = TRUE)
  else if (!is.null(col) & length(col) == 2) cols.levels(col[1], col[2], levels, fill =
    TRUE) else col.levels("blue", levels, fill = TRUE),
  col = NULL,
  col_interval = "white",
  col_fading_interval = 0.5,
  mfrow = NULL,
  Xlab = NULL,
  ylab = NULL,
  Xlim = if (!add) matrix(c(0, 1), 2, 2) else NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
```

```

    add_fading = 0.5,
    ...
)

## S3 method for class 'km'
filledcontourview(
  km_model,
  type = "UK",
  center = NULL,
  axis = NULL,
  npoints = 21,
  levels = pretty(c(km_model@y + 2 * sqrt(km_model@covariance@sd2), km_model@y - 2 *
    sqrt(km_model@covariance@sd2)), 10),
  col_points = if (!is.null(col) & length(col) == 1) col else "red",
  col_levels = if (!is.null(col) & length(col) == 1) col.levels(col, levels, fill = TRUE)
    else if (!is.null(col) & length(col) == 2) cols.levels(col[1], col[2], levels, fill =
    TRUE) else col.levels("blue", levels, fill = TRUE),
  col = NULL,
  conf_level = 0.5,
  conf_fading = 0.5,
  bg_fading = 1,
  mfrow = NULL,
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  ...
)

## S3 method for class 'Kriging'
filledcontourview(
  Kriging_model,
  center = NULL,
  axis = NULL,
  npoints = 21,
  levels = pretty(Kriging_model$y(), 10),
  col_points = if (!is.null(col) & length(col) == 1) col else "red",
  col_levels = if (!is.null(col) & length(col) == 1) col.levels(col, levels, fill = TRUE)
    else if (!is.null(col) & length(col) == 2) cols.levels(col[1], col[2], levels, fill =
    TRUE) else col.levels("blue", levels, fill = TRUE),
  col = NULL,
  conf_level = 0.5,
  conf_fading = 0.5,
  bg_fading = 1,
  mfrow = NULL,

```

```

Xlab = NULL,
ylab = NULL,
Xlim = NULL,
ylim = NULL,
title = NULL,
title_sep = " | ",
add = FALSE,
...
)

## S3 method for class 'WarpKriging'
filledcontourview(
  WarpKriging_model,
  center = NULL,
  axis = NULL,
  npoints = 21,
  levels = pretty(WarpKriging_model$y(), 10),
  col_points = if (!is.null(col) & length(col) == 1) col else "red",
  col_levels = if (!is.null(col) & length(col) == 1) col.levels(col, levels, fill = TRUE)
    else if (!is.null(col) & length(col) == 2) cols.levels(col[1], col[2], levels, fill =
      TRUE) else col.levels("blue", levels, fill = TRUE),
  col = NULL,
  conf_level = 0.5,
  conf_fading = 0.5,
  bg_fading = 1,
  mfrow = NULL,
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  ...
)

## S3 method for class 'glm'
filledcontourview(
  glm_model,
  center = NULL,
  axis = NULL,
  npoints = 21,
  levels = pretty(glm_model$fitted.values, 10),
  col_points = if (!is.null(col) & length(col) == 1) col else "red",
  col_levels = if (!is.null(col) & length(col) == 1) col.levels(col, levels, fill = TRUE)
    else if (!is.null(col) & length(col) == 2) cols.levels(col[1], col[2], levels, fill =
      TRUE) else col.levels("blue", levels, fill = TRUE),
  col = NULL,

```

```

    conf_level = 0.5,
    conf_fading = 0.5,
    bg_fading = 1,
    mfrow = NULL,
    Xlab = NULL,
    ylab = NULL,
    Xlim = NULL,
    ylim = NULL,
    title = NULL,
    title_sep = " | ",
    add = FALSE,
    ...
)

## S3 method for class 'list'
filledcontourview(
  modelFit_model,
  center = NULL,
  axis = NULL,
  npoints = 21,
  levels = pretty(modelFit_model$data$Y, 10),
  col_points = if (!is.null(col) & length(col) == 1) col else "red",
  col_levels = if (!is.null(col) & length(col) == 1) col.levels(col, levels, fill = TRUE)
    else if (!is.null(col) & length(col) == 2) cols.levels(col[1], col[2], levels, fill =
      TRUE) else col.levels("blue", levels, fill = TRUE),
  col = NULL,
  bg_fading = 1,
  mfrow = NULL,
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  ...
)

filledcontourview(...)

```

Arguments

fun	a function or 'predict()'-like function that returns a simple numeric or mean and standard error: list(mean=...,se=...).
vectorized	is fun vectorized?
center	optional coordinates (as a list or data frame) of the center of the section view if the model's dimension is > 2.
lty_center	line type for thesection center of the plot (if any).

<code>col_center</code>	color for the section center of the plot (if any).
<code>axis</code>	optional matrix of 2-axis combinations to plot, one by row. The value NULL leads to all possible combinations i.e. <code>choose(D, 2)</code> .
<code>npoints</code>	an optional number of points to discretize plot of response surface and uncertainties.
<code>levels</code>	(number of) contour levels to display.
<code>lty_levels</code>	contour line type.
<code>col_levels</code>	color for the surface.
<code>col</code>	color of the object (use <code>col_*</code> for specific objects).
<code>col_interval</code>	color to display interval width.
<code>col_fading_interval</code>	an optional factor of alpha (color channel) fading used to plot function output intervals (if any).
<code>mfrow</code>	an optional list to force <code>par(mfrow = ...)</code> call. The default value NULL is automatically set for compact view.
<code>Xlab</code>	an optional list of string to overload names for X.
<code>ylab</code>	an optional string to overload name for y.
<code>Xlim</code>	an optional list to force x range for all plots. The default value NULL is automatically set to include all design points.
<code>ylim</code>	an optional list to force y range for all plots.
<code>title</code>	an optional overload of main title.
<code>title_sep</code>	customize subtitle with fixed input.
<code>add</code>	to print graphics on an existing window.
<code>add_fading</code>	an optional factor of alpha (color channel) fading used to plot when <code>add=TRUE</code> .
<code>...</code>	arguments of the <code>filledcontourview.km</code> , <code>filledcontourview.glm</code> , <code>filledcontourview.Kriging</code> or <code>filledcontourview.function</code> function
<code>km_model</code>	an object of class "km".
<code>type</code>	the kriging type to use for model prediction.
<code>col_points</code>	color of points.
<code>conf_level</code>	confidence hulls to display.
<code>conf_fading</code>	an optional factor of alpha (color channel) fading used to plot confidence hull.
<code>bg_fading</code>	an optional factor of alpha (color channel) fading used to plot design points outside from this section.
<code>Kriging_model</code>	an object of class "Kriging".
<code>WarpKriging_model</code>	an object of class "WarpKriging".
<code>glm_model</code>	an object of class "glm".
<code>modelFit_model</code>	an object returned by <code>DiceEval::modelFit</code> .

Details

If available, experimental points are plotted with fading colors. Points that fall in the specified section (if any) have the color specified `col_points` while points far away from the center have shaded versions of the same color. The amount of fading is determined using the Euclidean distance between the plotted point and center.

Author(s)

Yann Richet, ASNR

See Also

[sectionview.function](#) for a section plot, and [sectionview3d.function](#) for a 2D section plot.
[sectionview.km](#) for a section plot, and [sectionview3d.km](#) for a 2D section plot.
[sectionview.Kriging](#) for a section plot, and [sectionview3d.Kriging](#) for a 2D section plot.
[sectionview.WarpKriging](#) for a section plot, and [sectionview3d.WarpKriging](#) for a 2D section plot.
[sectionview.glm](#) for a section plot, and [sectionview3d.glm](#) for a 2D section plot.

Examples

```
x1 <- rnorm(15)
x2 <- rnorm(15)

y <- x1 + x2 + rnorm(15)
model <- lm(y ~ x1 + x2)

filledcontourview(function(x) sum(x),
                  xlim=cbind(range(x1),range(x2)), col='black')
points(x1,x2)

filledcontourview(function(x) {
  x = as.data.frame(x)
  colnames(x) <- all.vars(model$call)[-1]
  predict.lm(model, newdata=x, se.fit=FALSE)
}, vectorized=TRUE, dim=2,
  xlim=cbind(range(x1),range(x2)), add=TRUE)

if (requireNamespace("DiceKriging")) { library(DiceKriging)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

model <- km(design = X, response = y, covtype="matern3_2")

filledcontourview(model)

}

if (requireNamespace("rlikkriging")) { library(rlikkriging)
```

```

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

model <- Kriging(X = X, y = y, kernel="matern3_2")

filledcontourview(model)

}

if (requireNamespace("rlikkriging")) { library(rlikkriging)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin) + 5*rnorm(15)

model <- WarpKriging(y = y, X = X, warping = c("affine","affine"), kernel="matern3_2")

filledcontourview(model)

}

x1 <- rnorm(15)
x2 <- rnorm(15)

y <- x1 + x2^2 + rnorm(15)
model <- glm(y ~ x1 + I(x2^2))

filledcontourview(model)

if (requireNamespace("DiceEval")) { library(DiceEval)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

model <- modelFit(X, y, type = "StepLinear")

filledcontourview(model)

}

## A 2D example - Branin-Hoo function
filledcontourview(branin, levels=30, col='black')

## Not run:
## a 16-points factorial design, and the corresponding response
d <- 2; n <- 16
design.fact <- expand.grid(seq(0, 1, length = 4), seq(0, 1, length = 4))
design.fact <- data.frame(design.fact); names(design.fact) <- c("x1", "x2")
y <- branin(design.fact); names(y) <- "y"

if (requireNamespace("DiceKriging")) { library(DiceKriging)
## model: km
model <- DiceKriging::km(design = design.fact, response = y)

```

```

filledcontourview(model, levels=30)
filledcontourview(branin, levels=30, col='red', add=TRUE)
}

if (requireNamespace("rlikriging")) { library(rlikriging)
## model: Kriging
model <- Kriging(X = as.matrix(design.fact), y = as.matrix(y), kernel="matern3_2")
filledcontourview(model, levels=30)
filledcontourview(branin, levels=30, col='red', add=TRUE)
}

## model: glm
model <- glm(y ~ 1+ x1 + x2 + I(x1^2) + I(x2^2) + x1*x2, data=cbind(y,design.fact))
filledcontourview(model, levels=30)
filledcontourview(branin, levels=30, col='red', add=TRUE)

if (requireNamespace("DiceEval")) { library(DiceEval)
## model: StepLinear
model <- modelFit(design.fact, y, type = "StepLinear")
filledcontourview(model, levels=30)
filledcontourview(branin, levels=30, col='red', add=TRUE)
}

## End(Not run)

```

is.mesh

Checks if a mesh is valid

Description

Checks if a mesh is valid

Usage

```
is.mesh(x)
```

Arguments

x mesh to check

Value

TRUE if mesh is valid

is_in.mesh	<i>Checks if some point belongs to a given mesh</i>
------------	---

Description

Checks if some point belongs to a given mesh

Usage

```
is_in.mesh(x, mesh)
```

Arguments

x	point to check
mesh	mesh identifying the set which X may belong

Examples

```
is_in.mesh(-0.5,mesh=geometry::delaunayn(matrix(c(0,1),ncol=1),output.options =TRUE))
is_in.mesh(0.5,mesh=geometry::delaunayn(matrix(c(0,1),ncol=1),output.options =TRUE))

x =matrix(-.5,ncol=2,nrow=1)
is_in.mesh(x,mesh=geometry::delaunayn(matrix(c(0,0,1,1,0,0),ncol=2),output.options =TRUE))

x =matrix(.5,ncol=2,nrow=1)
is_in.mesh(x,mesh=geometry::delaunayn(matrix(c(0,0,1,1,0,0),ncol=2),output.options =TRUE))
```

is_in.p	<i>Test if points are in a hull</i>
---------	-------------------------------------

Description

Test if points are in a hull

Usage

```
is_in.p(x, p, h = NULL)
```

Arguments

x	points to test
p	points defining the hull
h	hull itself (built from p if given as NULL (default))

Examples

```

is_in.p(x=-0.5,p=matrix(c(0,1),ncol=1))
is_in.p(x=0.5,p=matrix(c(0,1),ncol=1))
is_in.p(x=matrix(-.5,ncol=2,nrow=1),p=matrix(c(0,0,1,1,0,0),ncol=2))
is_in.p(x=matrix(.25,ncol=2,nrow=1),p=matrix(c(0,0,1,1,0,0),ncol=2))
is_in.p(x=matrix(-.5,ncol=3,nrow=1),p=matrix(c(0,0,0,1,0,0,0,1,0,0,0,1),ncol=3,byrow = TRUE))
is_in.p(x=matrix(.25,ncol=3,nrow=1),p=matrix(c(0,0,0,1,0,0,0,1,0,0,0,1),ncol=3,byrow = TRUE))

```

load3d

*Select/get the 3D engine used by DiceView***Description**

Public, stable entry point to select (if package is given) or auto-detect (if package is NULL) the 3D rendering package ("rgl" or "scatterplot3d") used by DiceView's *3d functions. This is the documented replacement for the internal `DiceView:::load3d()`, which is not part of the public API and should not be relied upon in user scripts.

Usage

```
load3d(package = NULL)
```

Arguments

package	name of the 3D package to use ("rgl" or "scatterplot3d"), or NULL to auto-select the first available one.
---------	---

Value

the name of the selected 3D package, or NULL (with a warning) if none is available.

Examples

```
load3d()
```

Memoize.function

*Memoize a function***Description**

Before each call of a function, check that the cache holds the results and returns it if available. Otherwise, compute `f` and cache the result for next evaluations.

Usage

```
Memoize.function(fun, suffix = ".RcacheDiceView")
```

Arguments

- fun function to memoize
- suffix suffix to use for cache files (default ".RcacheDiceView")

Value

a function with same behavior than argument one, but using cache.

Examples

```
f=function(n) rnorm(n);
F=Memoize.function(f);
F(5); F(6); F(5)
```

mesh	<i>Builds a mesh from a design aor set of points</i>
------	--

Description

Builds a mesh from a design aor set of points

Usage

```
mesh(intervals, mesh.type = "seq", mesh.sizes = 11)
```

Arguments

- intervals bounds to inverse in, each column contains min and max (or values) of each dimension
- mesh.type function or "unif" or "seq" (default) or "LHS" to preform interval partition
- mesh.sizes number of parts for mesh (duplicate for each dimension if using "seq")

Value

delaunay mesh (list(p,tri,...) from geometry)

Examples

```
mesh = mesh(intervals=matrix(c(0,1,0,1),ncol=2),mesh.type="unif",mesh.sizes=10)
plot2d_mesh(mesh)
```

mesh_exsets

Search excursion set of nD function, sampled by a mesh

Description

Search excursion set of nD function, sampled by a mesh

Usage

```
mesh_exsets(
    f,
    vectorized = FALSE,
    threshold,
    sign,
    intervals,
    mesh.type = "seq",
    mesh.sizes = 11,
    maxerror_f = 1e-09,
    tol = .Machine$double.eps^0.25,
    ex_filter.tri = all,
    num_workers = maxWorkers(),
    ...
)
```

Arguments

f	Function to inverse at 'threshold'
vectorized	boolean: is f already vectorized ? (default: FALSE) or if function: vectorized version of f.
threshold	target value to inverse
sign	focus at conservative for above (sign=1) or below (sign=-1) the threshold
intervals	bounds to inverse in, each column contains min and max of each dimension
mesh.type	"unif" or "seq" (default) or "LHS" to preform interval partition
mesh.sizes	number of parts for mesh (duplicate for each dimension if using "seq")
maxerror_f	maximal tolerance on f precision
tol	the desired accuracy (convergence tolerance on f arg).
ex_filter.tri	boolean function to validate a geometry::tri as considered in excursion : 'any' or 'all'
num_workers	number of cores to use for parallelization
...	parameters to forward to roots_mesh(...) call

Examples

```
# mesh_exsets(function(x) x, threshold=.51, sign=1, intervals=rbind(0,1),
# maxerror_f=1E-2,tol=1E-2, num_workers=1) # for faster testing
# mesh_exsets(function(x) x, threshold=.50000001, sign=1, intervals=rbind(0,1),
# maxerror_f=1E-2,tol=1E-2, num_workers=1) # for faster testing
# mesh_exsets(function(x) sum(x), threshold=.51,sign=1, intervals=cbind(rbind(0,1),rbind(0,1)),
# maxerror_f=1E-2,tol=1E-2, num_workers=1) # for faster testing
# mesh_exsets(sin,threshold=0,sign="sup",interval=c(pi/2,5*pi/2),
# maxerror_f=1E-2,tol=1E-2, num_workers=1) # for faster testing

if (identical(Sys.getenv("NOT_CRAN"), "true")) { # too long for CRAN on Windows

  e = mesh_exsets(function(x) (0.25+x[1])^2+(0.5+x[2])^2 ,
    threshold =0.25,sign=-1, intervals=matrix(c(-1,1,-1,1),nrow=2),
    maxerror_f=1E-2,tol=1E-2, # for faster testing
    num_workers=1)

  plot(e$p,xlim=c(-1,1),ylim=c(-1,1));
  apply(e$tri,1,function(tri) polygon(e$p[tri,],col=rgb(.4,.4,.4)))
  apply(e$frontiers,1,function(front) lines(e$p[front,],col='red'))

  if (requireNamespace("rgl")) {
    e = mesh_exsets(function(x) (0.5+x[1])^2+(-0.5+x[2])^2+(0.+x[3])^2,
      threshold = .25,sign=-1, mesh.type="unif",
      intervals=matrix(c(-1,1,-1,1,-1,1),nrow=2),
      maxerror_f=1E-2,tol=1E-2, # for faster testing
      num_workers=1)

    rgl::plot3d(e$p,xlim=c(-1,1),ylim=c(-1,1),zlim=c(-1,1));
    apply(e$tri,1,function(tri)rgl::lines3d(e$p[tri,]))
  }
}
```

mesh_level

Mesh level set of function

Description

Mesh level set of function

Usage

```
mesh_level(f, vectorized = FALSE, level = 0, intervals, mesh, ...)
```

Arguments

f	function to be evaluated on the mesh
vectorized	logical or function. If TRUE, f is assumed to be vectorized.
level	level/threshold value

intervals	matrix of intervals
mesh	mesh object or type
...	additional arguments passed to f

min_dist	<i>Minimal distance between one point to many points</i>
----------	--

Description

Minimal distance between one point to many points

Usage

```
min_dist(x, X, norm = rep(1, ncol(X)))
```

Arguments

x	one point
X	matrix of points (same number of columns than x)
norm	normalization vecor of distance (same number of columns than x)

Value

minimal distance

Examples

```
min_dist(runif(3),matrix(runif(30),ncol=3))
```

min_dist.mesh	<i>Compute distance between a point and a mesh</i>
---------------	--

Description

Compute distance between a point and a mesh

Usage

```
min_dist.mesh(p, mesh, norm = rep(1, ncol(mesh$p)))
```

Arguments

p	point to compute distance from
mesh	mesh to compute distance to
norm	vector of weights for each dimension (default: 1)

Value

distance between x and mesh

Examples

```
x = matrix(0,ncol=2)
m = list(p = matrix(c(0,1,1,0,1,1),ncol=2,byrow=TRUE), tri = matrix(c(1,2,3),nrow=1))
plot2d_mesh(m)
points(x)
min = min_dist.mesh(x,m)
lines(rbind(x,attr(min,"proj")),col='red')

m = mesh_exsets(function(x) (0.25+x[1])^2+(0.5+x[2]/2)^2, vec=FALSE,
                 1,1, intervals=rbind(cbind(0,0),cbind(1,1)), num_workers=1)
plot2d_mesh(m)
x = matrix(c(0.25,0.25),ncol=2)
points(x)
min = min_dist.mesh(x,m)
lines(rbind(x,attr(min,"proj")),col='red')
```

optim.stop

Title optim wrapper for early stopping criterion

Description

Title optim wrapper for early stopping criterion

Usage

```
optim.stop(
  par,
  fn,
  gr = NULL,
  fn.stop = NA,
  fn.NaN = NaN,
  control = list(),
  ...
)
```

Arguments

par	starting point for optim
fn	objective function, like in optim().
gr	gradient function, like in optim().
fn.stop	early stopping criterion
fn.NaN	replacement value of fn when returns NaN
control	control parameters for optim()
...	additional arguments passed to optim()

Value

list with best solution and all solutions

Author(s)

Yann Richet, ASNR

Examples

```
fn = function(x) x^6
o = optim( par=15, fn,lower=-20,upper=20,method='L-BFGS-B')
o.s = optim.stop( par=15, fn,lower=-20,upper=20,method='L-BFGS-B',fn.stop=0.1)
#check o.s$value == 0.1 && o.s$counts < o$counts
```

optims	<i>Title Multi-local optimization wrapper for optim, using (possibly parallel) multistart.</i>
--------	--

Description

Title Multi-local optimization wrapper for optim, using (possibly parallel) multistart.

Usage

```
optims(
  pars,
  fn,
  fn.NaN = NaN,
  fn.stop = NA,
  .apply = "mclapply",
  pars.eps = 1e-05,
  control = list(),
  ...
)
```

Arguments

<code>pars</code>	starting points for optim
<code>fn</code>	objective function, like in <code>optim()</code> .
<code>fn.NaN</code>	replacement value of <code>fn</code> when returns <code>NaN</code>
<code>fn.stop</code>	early stopping criterion
<code>.apply</code>	loop/parallelization backend for multistart ("mclapply", "lapply" or "foreach"). "mclapply" forks the current R process and is not safe when combined with a threaded BLAS/OpenMP library (this can deadlock); use <code>options(mc.cores=1)</code> or set the environment variable <code>OMP_THREAD_LIMIT=1</code> to force a fallback to sequential evaluation (see safe_mclapply), or pass <code>.apply="lapply"</code> to opt out of forking altogether.

pars.eps	minimal distance between two solutions to be considered different
control	control parameters for optim()
...	additional arguments passed to optim()

Value

list with best solution and all solutions

Author(s)

Yann Richet, ASNR

Examples

```
fn = function(x) ifelse(x==0,1,sin(x)/x)
# plot(fn, xlim=c(-20,20))
optim( par=5, fn, lower=-20, upper=20, method='L-BFGS-B')
optims(pars=t(t(seq(-20,20,,20))), fn, lower=-20, upper=20, method='L-BFGS-B')

# Branin function (3 local minimas)
f = function (x) {
  x1 <- x[1] * 15 - 5
  x2 <- x[2] * 15
  (x2 - 5/(4 * pi^2) * (x1^2) + 5/pi * x1 - 6)^2 + 10 * (1 - 1/(8 * pi)) * cos(x1) + 10
}
# expect to find 3 local minimas
optims(pars=matrix(runif(100),ncol=2),f,method="L-BFGS-B",lower=c(0,0),upper=c(1,1))
```

parview.function	<i>Parallel coordinates view of a prediction model or function.</i>
------------------	---

Description

Renders a parallel coordinates chart showing all input dimensions and the output simultaneously. Lines are colored by the output value (viridis palette), making it easy to identify which input regions drive high or low responses.

For model-based methods (km, Kriging, WarpKriging, glm, list) a space-filling LHS prediction grid is displayed together with the observed design points (in col_points color). Kriging-based methods also add y_low / y_up axes for the predictive confidence interval.

Two rendering engines are available via the engine argument:

"parallelPlot" Interactive htmlwidget (default), requires the **parallelPlot** package.

"base" Static base-R plot, no extra dependency.

Usage

```
## S3 method for class ``function``
parview(
  fun,
  vectorized = FALSE,
  n_points = 500,
  xlim = c(0, 1),
  col_fun = if (!is.null(col)) col else "blue",
  col = NULL,
  xlab = NULL,
  ylab = "y",
  engine = "parallelPlot",
  ...
)

## S3 method for class 'matrix'
parview(
  X,
  y,
  col_fun = if (!is.null(col)) col else "blue",
  col_points = if (!is.null(col)) col else "red",
  col = NULL,
  xlab = NULL,
  ylab = NULL,
  engine = "parallelPlot",
  ...
)

## S3 method for class 'Kriging'
parview(
  Kriging_model,
  n_points = 500,
  col_fun = if (!is.null(col)) col else "blue",
  col_points = if (!is.null(col)) col else "red",
  col = NULL,
  conf_level = 0.95,
  xlab = NULL,
  ylab = NULL,
  xlim = NULL,
  engine = "parallelPlot",
  ...
)

## S3 method for class 'WarpKriging'
parview(
  WarpKriging_model,
  n_points = 500,
  col_fun = if (!is.null(col)) col else "blue",
```

```

    col_points = if (!is.null(col)) col else "red",
    col = NULL,
    conf_level = 0.95,
    Xlab = NULL,
    ylab = NULL,
    Xlim = NULL,
    engine = "parallelPlot",
    ...
)

```

```
## S3 method for class 'km'
```

```

parview(
  km_model,
  type = "UK",
  n_points = 500,
  col_fun = if (!is.null(col)) col else "blue",
  col_points = if (!is.null(col)) col else "red",
  col = NULL,
  conf_level = 0.95,
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  engine = "parallelPlot",
  ...
)

```

```
## S3 method for class 'glm'
```

```

parview(
  glm_model,
  n_points = 500,
  col_fun = if (!is.null(col)) col else "blue",
  col_points = if (!is.null(col)) col else "red",
  col = NULL,
  conf_level = 0.95,
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  engine = "parallelPlot",
  ...
)

```

```
## S3 method for class 'list'
```

```

parview(
  modelFit_model,
  n_points = 500,
  col_fun = if (!is.null(col)) col else "blue",
  col_points = if (!is.null(col)) col else "red",
  col = NULL,

```

```

    Xlab = NULL,
    ylab = NULL,
    Xlim = NULL,
    engine = "parallelPlot",
    ...
)

parview(...)

```

Arguments

fun	a function or 'predict()' -like function that returns a simple numeric, or a list(mean=...,se=...).
vectorized	is fun vectorized?
n_points	number of LHS prediction points.
Xlim	optional input bounds matrix (2 x D); defaults to design range.
col_fun	base color for the prediction color scale (HSV saturation ramp from white to this color, matching the contourview policy).
col	shorthand alias for both col_fun and col_points; overridden by the individual arguments if both are supplied.
Xlab	optional character vector of axis labels for inputs.
ylab	optional string label for the output axis.
engine	rendering engine: "parallelPlot" or "base".
...	arguments of the relevant parview.* method.
X	the matrix of input design.
y	the array of output values.
col_points	color of observed design points.
Kriging_model	an object of class "Kriging".
conf_level	confidence level for uncertainty bands shown as extra axes.
WarpKriging_model	an object of class "WarpKriging".
km_model	an object of class "km".
type	the kriging type to use for model prediction.
glm_model	an object of class "glm".
modelFit_model	an object returned by DiceEval::modelFit.

See Also

[sectionview.function](#) for 1D section plots.
[sectionview.matrix](#) for 1D section plots.
[sectionview.Kriging](#) for 1D section plots.
[sectionview.WarpKriging](#) for 1D section plots.
[sectionview.km](#) for 1D section plots.
[sectionview.glm](#) for 1D section plots.
[sectionview.list](#) for 1D section plots.

Examples

```

parview(branin, Xlim = rbind(c(0, 0), c(1, 1)), engine = "base")
X <- matrix(runif(15 * 2), ncol = 2)
y <- apply(X, 1, branin)
parview(X, y, engine = "base")
if (requireNamespace("rlikkriging")) { library(rlikkriging)
  X <- matrix(runif(15 * 2), ncol = 2)
  y <- apply(X, 1, branin)
  model <- Kriging(X = X, y = as.matrix(y), kernel = "matern3_2")
  parview(model, engine = "base")
}
if (requireNamespace("rlikkriging")) { library(rlikkriging)
  X <- matrix(runif(15 * 2), ncol = 2)
  y <- apply(X, 1, branin) + 5 * rnorm(15)
  model <- WarpKriging(y = y, X = X, warping = c("affine", "affine"), kernel = "matern3_2")
  parview(model, engine = "base")
}
if (requireNamespace("DiceKriging")) { library(DiceKriging)
  X <- matrix(runif(15 * 2), ncol = 2)
  y <- apply(X, 1, branin)
  model <- km(design = X, response = y, covtype = "matern3_2")
  parview(model, engine = "base")
}
x1 <- rnorm(15); x2 <- rnorm(15)
y <- x1 + x2^2 + rnorm(15)
model <- glm(y ~ x1 + I(x2^2))
parview(model, engine = "base")
if (requireNamespace("DiceEval")) { library(DiceEval)
  X <- matrix(runif(15 * 2), ncol = 2)
  y <- apply(X, 1, branin)
  model <- modelFit(X, y, type = "StepLinear")
  parview(model, engine = "base")
}
## Static base-R plot
parview(branin, Xlim = rbind(c(0, 0), c(1, 1)), engine = "base")

## Design points only
X <- matrix(runif(30 * 2), ncol = 2)
y <- apply(X, 1, branin)
parview(X, y, engine = "base")

```

plot_mesh

Plot a one dimensional mesh

Description

Plot a one dimensional mesh

Usage

```

plot_mesh(
  mesh,
  y = 0,
  color.nodes = "black",
  color.mesh = "darkgray",
  alpha = 0.4,
  ...
)

```

Arguments

mesh	1-dimensional mesh to draw
y	ordinate value where to draw the mesh
color.nodes	color of the mesh nodes
color.mesh	color of the mesh elements
alpha	transparency of the mesh elements & nodes
...	optional arguments passed to plot function

Examples

```

plot_mesh(mesh_exsets(function(x) x, threshold=.51, sign=1,
  intervals=rbind(0,1), num_workers=1))
plot_mesh(mesh_exsets(function(x) (x-.5)^2, threshold=.1, sign=-1,
  intervals=rbind(0,1), num_workers=1))

```

plot2d_mesh	<i>Plot a two dimensional mesh</i>
-------------	------------------------------------

Description

Plot a two dimensional mesh

Usage

```

plot2d_mesh(
  mesh,
  color.nodes = "black",
  color.mesh = "darkgray",
  alpha = 0.4,
  ...
)

```

Arguments

mesh	2-dimensional mesh to draw
color.nodes	color of the mesh nodes
color.mesh	color of the mesh elements
alpha	transparency of the mesh elements & nodes
...	optional arguments passed to plot function

Examples

```
plot2d_mesh(mesh_exsets(f = function(x) sin(pi*x[1])*sin(pi*x[2]),
                        threshold=0,sign=1, mesh.type="unif",mesh.size=11,
                        intervals = matrix(c(1/2,5/2,1/2,5/2),nrow=2),
                        num_workers=1))
```

plot3d_mesh	<i>Plot a three dimensional mesh</i>
-------------	--------------------------------------

Description

Plot a three dimensional mesh

Usage

```
plot3d_mesh(
  mesh,
  engine3d = NULL,
  color.nodes = "black",
  color.mesh = "darkgray",
  alpha = 0.4,
  ...
)
```

Arguments

mesh	3-dimensional mesh to draw
engine3d	3d framework to use: 'rgl' if installed or 'scatterplot3d' (default)
color.nodes	color of the mesh nodes
color.mesh	color of the mesh elements
alpha	transparency of the mesh elements & nodes
...	optional arguments passed to plot function

Examples

```

if (identical(Sys.getenv("NOT_CRAN"), "true")) { # too long for CRAN on Windows

  plot3d_mesh(mesh_exsets(function(x) (0.5+x[1])^2+(-0.5+x[2])^2+(0.+x[3])^2,
    threshold = .25,sign=-1, mesh.type="unif",
    maxerror_f=1E-2,tol=1E-2, # faster display
    intervals=matrix(c(-1,1,-1,1,-1,1),nrow=2),
    num_workers=1),
    engine3d='scatterplot3d')

  if (requireNamespace("rgl")) {
    plot3d_mesh(mesh_exsets(function(x) (0.5+x[1])^2+(-0.5+x[2])^2+(0.+x[3])^2,
      threshold = .25,sign=-1, mesh.type="unif",
      maxerror_f=1E-2,tol=1E-2, # faster display
      intervals=matrix(c(-1,1,-1,1,-1,1),nrow=2),
      num_workers=1),engine3d='rgl')
  }
}

```

points_in.mesh	<i>Extract points of mesh which belong to the mesh triangulation (may not contain all points)</i>
----------------	---

Description

Extract points of mesh which belong to the mesh triangulation (may not contain all points)

Usage

```
points_in.mesh(mesh)
```

Arguments

mesh	mesh (list(p,tri,...) from geometry)
------	--------------------------------------

Value

points coordinates inside the mesh triangulation

<code>points_out.mesh</code>	<i>Extract points of mesh which do not belong to the mesh triangulation (may not contain all points)</i>
------------------------------	--

Description

Extract points of mesh which do not belong to the mesh triangulation (may not contain all points)

Usage

```
points_out.mesh(mesh)
```

Arguments

<code>mesh</code>	(list(p,tri,...) from geometry)
-------------------	---------------------------------

Value

points coordinates outside the mesh triangulation

<code>root</code>	<i>One Dimensional Root (Zero) Finding</i>
-------------------	--

Description

Search one root with given precision (on y). Iterate over uniroot as long as necessary.

Usage

```
root(
  f,
  lower,
  upper,
  maxerror_f = 1e-07,
  f_lower = f(lower, ...),
  f_upper = f(upper, ...),
  tol = .Machine$double.eps^0.25,
  convexity = FALSE,
  rec = 0,
  max.rec = NA,
  ...
)
```

Arguments

f	the function for which the root is sought.
lower	the lower end point of the interval to be searched.
upper	the upper end point of the interval to be searched.
maxerror_f	the maximum error on f evaluation (iterates over uniroot to converge).
f_lower	the same as f(lower).
f_upper	the same as f(upper).
tol	the desired accuracy (convergence tolerance on f arg).
convexity	the learned convexity factor of the function, used to reduce the boundaries for uniroot.
rec	counter of recursive level.
max.rec	maximal number of recursive level before failure (stop).
...	additional named or unnamed arguments to be passed to f.

Author(s)

Yann Richet, ASNR

Examples

```
f=function(x) {cat("f");1-exp(x)}; f(root(f,lower=-1,upper=2))
f=function(x) {cat("f");exp(x)-1}; f(root(f,lower=-1,upper=2))

.f = function(x) 1-exp(1*x)
f=function(x) {cat("f");y=.f(x);points(x,y,pch=20,col=rgb(0,0,0,.2));y}
plot(.f,xlim=c(-1,2)); f(root(f,lower=-1,upper=2))

.f = function(x) exp(10*x)-1
f=function(x) {cat("f");y=.f(x);points(x,y,pch=20);y}
plot(.f,xlim=c(-1,2)); f(root(f,lower=-1,upper=2))

.f = function(x) exp(100*x)-1
f=function(x) {cat("f");y=.f(x);points(x,y,pch=20);y}
plot(.f,xlim=c(-1,2)); f(root(f,lower=-1,upper=2))

f=function(x) {cat("f");exp(100*x)-1}; f(root(f,lower=-1,upper=2))

## Not run:

# Quite hard functions to find roots

## Increasing function
## convex
n.f=0
.f = function(x) exp(10*x)-1
f=function(x) {n.f<-n.f+1;y=.f(x);points(x,y,pch=20);y}
plot(.f,xlim=c(-.1,.2)); f(root(f,lower=-1,upper=2))
print(n.f)
```

```

## non-convex
n.f=0
.f = function(x) 1-exp(-10*x)
f=function(x) {n.f<-n.f+1;y=.f(x);points(x,y,pch=20);y}
plot(.f,xlim=c(-.1,.2)); f(root(f,lower=-1,upper=2))
print(n.f)

# ## Decreasing function
# ## non-convex
n.f=0
.f = function(x) 1-exp(10*x)
f=function(x) {n.f<-n.f+1;y=.f(x);points(x,y,pch=20,col=rgb(0,0,0,.2));y}
plot(.f,xlim=c(-.1,.2)); f(root(f,lower=-1,upper=2))
print(n.f)
# ## convex
n.f=0
.f = function(x) exp(-10*x)-1
f=function(x) {n.f<-n.f+1;y=.f(x);points(x,y,pch=20,col=rgb(0,0,0,.2));y}
plot(.f,xlim=c(-.1,.2)); f(root(f,lower=-1,upper=2))
print(n.f)

## End(Not run)

```

roots

One Dimensional Multiple Roots (Zero) Finding

Description

Search multiple roots of 1D function, sampled/splitted by a (1D) mesh

Usage

```

roots(
  f,
  vectorized = FALSE,
  interval,
  maxerror_f = 1e-07,
  split = "seq",
  split.size = 11,
  tol = .Machine$double.eps^0.25,
  .lapply = safe_mclapply,
  ...
)

```

Arguments

f	Function to find roots
vectorized	boolean: is f already vectorized ? (default: FALSE) or if function: vectorized version of f.

interval	bounds to inverse in
maxerror_f	the maximum error on f evaluation (iterates over uniroot to converge).
split	function or "unif" or "seq" (default) to preform interval partition
split.size	number of parts to perform uniroot inside
tol	the desired accuracy (convergence tolerance on f arg).
.lapply	control the loop/vectorization over different roots (defaults to multicore apply).
...	additional named or unnamed arguments to be passed to f.

Value

array of x, so $f(x)=\text{target}$

Examples

```
roots(sin,interval=c(pi/2,5*pi/2))
roots(sin,interval=c(pi/2,1.5*pi/2))

f=function(x)exp(x)-1;
f(roots(f,interval=c(-1,2)))

f=function(x)exp(1000*x)-1;
f(roots(f,interval=c(-1,2)))
```

roots_mesh	<i>Multi Dimensional Multiple Roots (Zero) Finding, sampled by a mesh</i>
------------	---

Description

Multi Dimensional Multiple Roots (Zero) Finding, sampled by a mesh

Usage

```
roots_mesh(
  f,
  vectorized = FALSE,
  intervals,
  mesh.type = "seq",
  mesh.sizes = 11,
  maxerror_f = 1e-07,
  tol = .Machine$double.eps^0.25,
  num_workers = maxWorkers(),
  ...
)
```

Arguments

<code>f</code>	Function (one or more dimensions) to find roots of
<code>vectorized</code>	vectorized <code>f</code> : function, TRUE (use <code>f</code> directly), or wrap in <code>Vectorize.function</code> : FALSE (default args), "lapply", "mclapply", ...
<code>intervals</code>	bounds to inverse in, each column contains min and max of each dimension
<code>mesh.type</code>	function or "unif" or "seq" (default) to preform interval partition
<code>mesh.sizes</code>	number of parts for mesh (duplicate for each dimension if using "seq")
<code>maxerror_f</code>	the maximum error on <code>f</code> evaluation (iterates over <code>uniroot</code> to converge).
<code>tol</code>	the desired accuracy (convergence tolerance on <code>f</code> arg).
<code>num_workers</code>	number of parallel roots finding
<code>...</code>	Other args for <code>f</code>

Value

matrix of `x`, so `f(x)=0`

Examples

```

roots_mesh(function(x) x-.51, intervals=rbind(0,1),
  num_workers=1)
roots_mesh(function(x) sum(x)-.51, intervals=cbind(rbind(0,1),rbind(0,1)),
  num_workers=1)
roots_mesh(sin,intervals=c(pi/2,5*pi/2),
  num_workers=1)
roots_mesh(f = function(x) sin(pi*x[1])*sin(pi*x[2]),
  intervals = matrix(c(1/2,5/2,1/2,5/2),nrow=2),
  num_workers=1)

r = roots_mesh(f = function(x) (0.25+x[1])^2+(0.5+x[2])^2 - .25,
  intervals=matrix(c(-1,1,-1,1),nrow=2), mesh.size=5,
  num_workers=1)
plot(r,xlim=c(-1,1),ylim=c(-1,1))

r = roots_mesh(function(x) (0.5+x[1])^2+(-0.5+x[2])^2+(0.+x[3])^2 - .5,
  mesh.sizes = 11,
  intervals=matrix(c(-1,1,-1,1,-1,1),nrow=2),
  num_workers=1)
scatterplot3d::scatterplot3d(r,xlim=c(-1,1),ylim=c(-1,1),zlim=c(-1,1))

roots_mesh(function(x)exp(x)-1,intervals=c(-1,2),
  num_workers=1)
roots_mesh(function(x)exp(1000*x)-1,intervals=c(-1,2),
  num_workers=1)

```

safe_mclapply	<i>Fork-safe parallel lapply</i>
---------------	----------------------------------

Description

Drop-in replacement for `parallel::mclapply` that prevents deadlocks from nested fork calls. Uses an R option (`.DiceView_parallel_depth`) inherited by forked children to detect nesting and fall back to `lapply` in that case. This avoids the classic pipe deadlock where a forked worker tries to fork grandchildren while the parent is still waiting on pipes.

Usage

```
safe_mclapply(X, FUN, ..., mc.cores = getOption("mc.cores", maxWorkers()))
```

Arguments

X	a vector (atomic or list)
FUN	the function to be applied to each element of X
...	optional arguments to FUN
mc.cores	number of cores (default: <code>getOption("mc.cores", parallel::detectCores())</code>)

Value

list of results, like `lapply`

Examples

```
safe_mclapply(1:4, function(i) i^2)
# nested call falls back to lapply automatically:
outer <- safe_mclapply(1:2, function(i) safe_mclapply(1:3, function(j) i*j))
```

sectionview.function	<i>Plot a section view of a prediction model or function, including design points if available.</i>
----------------------	---

Description

Plot a section view of a prediction model or function, including design points if available.

Usage

```

## S3 method for class ``function``
sectionview(
  fun,
  vectorized = FALSE,
  center = NULL,
  lty_center = 2,
  col_center = "black",
  axis = NULL,
  npoints = 101,
  col_fun = if (!is.null(col)) col else "blue",
  col = NULL,
  col_fading_interval = 0.5,
  mfrow = NULL,
  Xlab = NULL,
  ylab = NULL,
  Xlim = if (!add) c(0, 1) else NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  ...
)

## S3 method for class 'matrix'
sectionview(
  X,
  y,
  center = NULL,
  lty_center = 2,
  col_center = "black",
  axis = NULL,
  col_points = if (!is.null(col)) col else "red",
  col = NULL,
  col_fading_interval = 0.5,
  bg_fading = 5,
  mfrow = NULL,
  Xlab = NULL,
  ylab = NULL,
  Xlim = if (!add) c(0, 1) else NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  ...
)

## S3 method for class 'character'

```

```
sectionview(eval_str, axis = NULL, mfrow = NULL, ...)
```

```
## S3 method for class 'km'
```

```
sectionview(  
  km_model,  
  type = "UK",  
  center = NULL,  
  axis = NULL,  
  npoints = 101,  
  col_points = if (!is.null(col)) col else "red",  
  col_fun = if (!is.null(col)) col else "blue",  
  col = NULL,  
  conf_level = 0.95,  
  conf_fading = 0.5,  
  bg_fading = 5,  
  mfrow = NULL,  
  Xlab = NULL,  
  ylab = NULL,  
  Xlim = NULL,  
  ylim = NULL,  
  title = NULL,  
  title_sep = " | ",  
  add = FALSE,  
  ...  
)
```

```
## S3 method for class 'Kriging'
```

```
sectionview(  
  Kriging_model,  
  center = NULL,  
  axis = NULL,  
  npoints = 101,  
  col_points = if (!is.null(col)) col else "red",  
  col_fun = if (!is.null(col)) col else "blue",  
  col = NULL,  
  conf_level = 0.95,  
  conf_fading = 0.5,  
  bg_fading = 5,  
  mfrow = NULL,  
  Xlab = NULL,  
  ylab = NULL,  
  Xlim = NULL,  
  ylim = NULL,  
  title = NULL,  
  title_sep = " | ",  
  add = FALSE,  
  ...  
)
```

```
## S3 method for class 'WarpKriging'
sectionview(
  WarpKriging_model,
  center = NULL,
  axis = NULL,
  npoints = 101,
  col_points = if (!is.null(col)) col else "red",
  col_fun = if (!is.null(col)) col else "blue",
  col = NULL,
  conf_level = 0.95,
  conf_fading = 0.5,
  bg_fading = 5,
  mfrow = NULL,
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  ...
)
```

```
## S3 method for class 'glm'
sectionview(
  glm_model,
  center = NULL,
  axis = NULL,
  npoints = 101,
  col_points = if (!is.null(col)) col else "red",
  col_fun = if (!is.null(col)) col else "blue",
  col = NULL,
  conf_level = 0.95,
  conf_fading = 0.5,
  bg_fading = 5,
  mfrow = NULL,
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  ...
)
```

```
## S3 method for class 'list'
```

```

sectionview(
  modelFit_model,
  center = NULL,
  axis = NULL,
  npoints = 101,
  col_points = if (!is.null(col)) col else "red",
  col_fun = if (!is.null(col)) col else "blue",
  col = NULL,
  bg_fading = 5,
  mfrow = NULL,
  Xlab = NULL,
  ylab = NULL,
  xlim = NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  ...
)

sectionview(...)

```

Arguments

fun	a function or 'predict()'-like function that returns a simple numeric, or an interval, or mean and standard error: list(mean=...,se=...).
vectorized	is fun vectorized?
center	optional coordinates (as a list or data frame) of the center of the section view if the model's dimension is > 2.
lty_center	line type for the section center of the plot (if any).
col_center	color for the section center of the plot (if any).
axis	optional matrix of 2-axis combinations to plot, one by row. The value NULL leads to all possible combinations i.e. choose(D, 2).
npoints	an optional number of points to discretize plot of response surface and uncertainties.
col_fun	color of the function plot.
col	color of the object (use col_* for specific objects).
col_fading_interval	an optional factor of alpha (color channel) fading used to plot confidence intervals.
mfrow	an optional list to force par(mfrow = . . .) call. The default value NULL is automatically set for compact view.
Xlab	an optional list of string to overload names for X.
ylab	an optional string to overload name for y.

Xlim	an optional list to force x range for all plots. The default value NULL is automatically set to include all design points.
ylim	an optional list to force y range for all plots.
title	an optional overload of main title.
title_sep	customize subtitle with fixed input.
add	to print graphics on an existing window.
...	arguments of the <code>sectionview.km</code> , <code>sectionview.glm</code> , <code>sectionview.Kriging</code> or <code>sectionview.function</code> function
X	the matrix of input design.
y	the array of output values (two columns means an interval).
col_points	color of points.
bg_fading	an optional factor of alpha (color channel) fading used to plot design points outside from this section.
eval_str	the expression to evaluate in each subplot.
km_model	an object of class "km".
type	the kriging type to use for model prediction.
conf_level	an optional list of confidence intervals to display.
conf_fading	an optional factor of alpha (color channel) fading used to plot confidence intervals.
Kriging_model	an object of class "Kriging".
WarpKriging_model	an object of class "WarpKriging".
glm_model	an object of class "glm".
modelFit_model	an object returned by <code>DiceEval::modelFit</code> .

Details

If available, experimental points are plotted with fading colors. Points that fall in the specified section (if any) have the color specified `col_points` while points far away from the center have shaded versions of the same color. The amount of fading is determined using the Euclidean distance between the plotted point and center.

Author(s)

Yann Richet, ASNR

See Also

[sectionview.function](#) for a section plot, and [sectionview3d.function](#) for a 2D section plot.
[sectionview.matrix](#) for a section plot, and [sectionview3d.matrix](#) for a 2D section plot.
[sectionview.km](#) for a section plot, and [sectionview3d.km](#) for a 2D section plot.
[sectionview.Kriging](#) for a section plot, and [sectionview3d.Kriging](#) for a 2D section plot.
[sectionview.Kriging](#) for a section plot, and [sectionview3d.WarpKriging](#) for a 2D section plot.
[sectionview.glm](#) for a section plot, and [sectionview3d.glm](#) for a 2D section plot.

Examples

```

x1 <- rnorm(15)
x2 <- rnorm(15)

y <- x1 + x2 + rnorm(15)
model <- lm(y ~ x1 + x2)

sectionview(function(x) sum(x),
             center=c(0,0), xlim=cbind(range(x1),range(x2)), col='black')

sectionview(function(x) {
  x = as.data.frame(x)
  colnames(x) <- all.vars(model$call)[-1]
  p = predict.lm(model, newdata=x, se.fit=TRUE)
  cbind(p$fit-1.96 * p$se.fit, p$fit+1.96 * p$se.fit)
}, vectorized=TRUE, add=TRUE)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

sectionview(X,y, center=c(.5,.5))

x1 <- rnorm(15)
x2 <- rnorm(15)

y <- x1 + x2^2 + rnorm(15)
model <- glm(y ~ x1 + I(x2^2))

sectionview(model, center=c(.5,.5))

sectionview("abline(h=5)")
if (requireNamespace("DiceKriging")) { library(DiceKriging)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

model <- km(design = X, response = y, covtype="matern3_2")

sectionview(model, center=c(.5,.5))

}

if (requireNamespace("rlikkriging")) { library(rlikkriging)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

model <- Kriging(X = X, y = y, kernel="matern3_2")

sectionview(model, center=c(.5,.5))

}

```

```

if (requireNamespace("rlikkriging")) { library(rlikkriging)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin) + 5*rnorm(15)

model <- WarpKriging(y = y, X = X, warping = c("affine","affine"), kernel="matern3_2")

sectionview(model, center=c(.5,.5))

}

x1 <- rnorm(15)
x2 <- rnorm(15)

y <- x1 + x2^2 + rnorm(15)
model <- glm(y ~ x1 + I(x2^2))

sectionview(model, center=c(.5,.5))

if (requireNamespace("DiceEval")) { library(DiceEval)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

model <- modelFit(X, y, type = "StepLinear")

sectionview(model, center=c(.5,.5))

}

## A 2D example - Branin-Hoo function
sectionview(branin, center= c(.5,.5), col='black')

## Not run:
## a 16-points factorial design, and the corresponding response
d <- 2; n <- 16
design.fact <- expand.grid(seq(0, 1, length = 4), seq(0, 1, length = 4))
design.fact <- data.frame(design.fact); names(design.fact) <- c("x1", "x2")
y <- branin(design.fact); names(y) <- "y"

if (requireNamespace("DiceKriging")) { library(DiceKriging)
## model: km
model <- DiceKriging::km(design = design.fact, response = y)
sectionview(model, center= c(.5,.5))
sectionview(branin, center= c(.5,.5), col='red', add=TRUE)
}

if (requireNamespace("rlikkriging")) { library(rlikkriging)
## model: Kriging
model <- Kriging(X = as.matrix(design.fact), y = as.matrix(y), kernel="matern3_2")
sectionview(model, center= c(.5,.5))
sectionview(branin, center= c(.5,.5), col='red', add=TRUE)
}

```

```

}

## model: glm
model <- glm(y ~ 1+ x1 + x2 + I(x1^2) + I(x2^2) + x1*x2, data=cbind(y,design.fact))
sectionview(model, center= c(.5,.5))
sectionview(branin, center= c(.5,.5), col='red', add=TRUE)

if (requireNamespace("DiceEval")) { library(DiceEval)
## model: StepLinear
model <- modelFit(design.fact, y, type = "StepLinear")
sectionview(model, center= c(.5,.5))
sectionview(branin, center= c(.5,.5), col='red', add=TRUE)
}

## End(Not run)

```

sectionview3d.function

Plot a contour view of a prediction model or function, including design points if available.

Description

Plot a contour view of a prediction model or function, including design points if available.

Usage

```

## S3 method for class ``function``
sectionview3d(
  fun,
  vectorized = FALSE,
  center = NULL,
  axis = NULL,
  npoints = 21,
  col_fun = if (!is.null(col)) col else "blue",
  col = NULL,
  col_fading_interval = 0.5,
  mfrow = c(1, 1),
  Xlab = NULL,
  Ylab = NULL,
  Xlim = if (!add) matrix(c(0, 1), 2, 2) else NULL,
  Ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  engine3d = NULL,
  ...

```

```

)

## S3 method for class 'matrix'
sectionview3d(
  X,
  y,
  center = NULL,
  axis = NULL,
  col_points = if (!is.null(col)) col else "red",
  col = NULL,
  col_fading_interval = 0.5,
  bg_fading = 1,
  mfrow = c(1, 1),
  Xlab = NULL,
  ylab = NULL,
  Xlim = if (!add) matrix(c(0, 1), 2, 2) else NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  engine3d = NULL,
  ...
)

## S3 method for class 'character'
sectionview3d(eval_str, axis = NULL, mfrow = c(1, 1), ...)

## S3 method for class 'km'
sectionview3d(
  km_model,
  type = "UK",
  center = NULL,
  axis = NULL,
  npoints = 21,
  col_points = if (!is.null(col)) col else "red",
  col_fun = if (!is.null(col)) col else "blue",
  col = NULL,
  conf_level = 0.95,
  conf_fading = 0.5,
  bg_fading = 1,
  mfrow = c(1, 1),
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,

```

```
    engine3d = NULL,
    ...
)

## S3 method for class 'Kriging'
sectionview3d(
  Kriging_model,
  center = NULL,
  axis = NULL,
  npoints = 21,
  col_points = if (!is.null(col)) col else "red",
  col_fun = if (!is.null(col)) col else "blue",
  col = NULL,
  conf_level = 0.95,
  conf_fading = 0.5,
  bg_fading = 1,
  mfrow = c(1, 1),
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  engine3d = NULL,
  ...
)

## S3 method for class 'WarpKriging'
sectionview3d(
  WarpKriging_model,
  center = NULL,
  axis = NULL,
  npoints = 21,
  col_points = if (!is.null(col)) col else "red",
  col_fun = if (!is.null(col)) col else "blue",
  col = NULL,
  conf_level = 0.95,
  conf_fading = 0.5,
  bg_fading = 1,
  mfrow = c(1, 1),
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
```

```

    engine3d = NULL,
    ...
)

## S3 method for class 'glm'
sectionview3d(
  glm_model,
  center = NULL,
  axis = NULL,
  npoints = 21,
  col_points = if (!is.null(col)) col else "red",
  col_fun = if (!is.null(col)) col else "blue",
  col = NULL,
  conf_level = 0.95,
  conf_fading = 0.5,
  bg_fading = 1,
  mfrow = c(1, 1),
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  engine3d = NULL,
  ...
)

## S3 method for class 'list'
sectionview3d(
  modelFit_model,
  center = NULL,
  axis = NULL,
  npoints = 21,
  col_points = if (!is.null(col)) col else "red",
  col_fun = if (!is.null(col)) col else "blue",
  col = NULL,
  bg_fading = 1,
  mfrow = c(1, 1),
  Xlab = NULL,
  ylab = NULL,
  Xlim = NULL,
  ylim = NULL,
  title = NULL,
  title_sep = " | ",
  add = FALSE,
  engine3d = NULL,
  ...
)

```

```
)
sectionview3d(...)
```

Arguments

fun	a function or 'predict()'-like function that returns a simple numeric, or an interval, or mean and standard error: list(mean=...,se=...).
vectorized	is fun vectorized?
center	optional coordinates (as a list or data frame) of the center of the section view if the model's dimension is > 2.
axis	optional matrix of 2-axis combinations to plot, one by row. The value NULL leads to all possible combinations i.e. choose(D, 2).
npoints	an optional number of points to discretize plot of response surface and uncertainties.
col_fun	color of the function plot.
col	color of the object (use col_* for specific objects).
col_fading_interval	an optional factor of alpha (color channel) fading used to plot confidence intervals.
mfrow	an optional list to force par(mfrow = . . .) call. The default value NULL is automatically set for compact view.
Xlab	an optional list of string to overload names for X.
ylab	an optional string to overload name for y.
Xlim	an optional list to force x range for all plots. The default value NULL is automatically set to include all design points (and their 1-99 percentiles).
ylim	an optional list to force y range for all plots. The default value NULL is automatically set to include all design points (and their 1-99 percentiles).
title	an optional overload of main title.
title_sep	customize subtitle with fixed input.
add	to print graphics on an existing window.
engine3d	3D view package to use. "rgl" if available, otherwise "scatterplot3d" by default.
...	arguments of the sectionview3d.km, sectionview3d.glm, sectionview3d.Kriging or sectionview3d.function function
X	the matrix of input design.
y	the array of output values (two columns means an interval).
col_points	color of points.
bg_fading	an optional factor of alpha (color channel) fading used to plot design points outside from this section.
eval_str	the expression to evaluate in each subplot.
km_model	an object of class "km".

<code>type</code>	the kriging type to use for model prediction.
<code>conf_level</code>	an optional list of confidence intervals to display.
<code>conf_fading</code>	an optional factor of alpha (color channel) fading used to plot confidence intervals.
<code>Kriging_model</code>	an object of class "Kriging".
<code>WarpKriging_model</code>	an object of class "WarpKriging".
<code>glm_model</code>	an object of class "glm".
<code>modelFit_model</code>	an object returned by <code>DiceEval::modelFit</code> .

Details

If available, experimental points are plotted with fading colors. Points that fall in the specified section (if any) have the color specified `col_points` while points far away from the center have shaded versions of the same color. The amount of fading is determined using the Euclidean distance between the plotted point and center.

Author(s)

Yann Richet, ASNR

See Also

[sectionview.function](#) for a section plot, and [sectionview3d.function](#) for a 2D section plot.
[sectionview.matrix](#) for a section plot, and [sectionview3d.matrix](#) for a 2D section plot.
[sectionview3d.matrix](#) for a section plot.
[sectionview.km](#) for a section plot, and [sectionview3d.km](#) for a 2D section plot.
[sectionview.Kriging](#) for a section plot, and [sectionview3d.Kriging](#) for a 2D section plot.
[sectionview.WarpKriging](#) for a section plot, and [sectionview3d.WarpKriging](#) for a 2D section plot.
[sectionview.glm](#) for a section plot, and [sectionview3d.glm](#) for a 2D section plot.

Examples

```
x1 <- rnorm(15)
x2 <- rnorm(15)

y <- x1 + x2 + rnorm(15)
model <- lm(y ~ x1 + x2)

sectionview3d(function(x) sum(x),
               xlim=cbind(range(x1),range(x2)), col='black')
DiceView:::.plot3d(x1, x2, y)

sectionview3d(function(x) {
  x = as.data.frame(x)
  colnames(x) <- all.vars(model$call)[-1]
```

```

        p = predict.lm(model, newdata=x, se.fit=TRUE)
        list(mean=p$fit, se=p$se.fit)
      }, vectorized=TRUE,
      add=TRUE)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

sectionview3d(X, y)

x1 <- rnorm(15)
x2 <- rnorm(15)

y <- x1 + x2^2 + rnorm(15)
model <- glm(y ~ x1 + I(x2^2))

sectionview3d(model)

sectionview3d("abline(h=0.25,col='red')")
if (requireNamespace("DiceKriging")) { library(DiceKriging)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

model <- km(design = X, response = y, covtype="matern3_2")

sectionview3d(model)

}

if (requireNamespace("rlikkriging")) { library(rlikkriging)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

model <- Kriging(X = X, y = y, kernel="matern3_2")

sectionview3d(model)

}

if (requireNamespace("rlikkriging")) { library(rlikkriging)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin) + 5*rnorm(15)

model <- WarpKriging(y = y, X = X, warping = c("affine","affine"), kernel="matern3_2")

sectionview3d(model)

}

x1 <- rnorm(15)

```

```

x2 <- rnorm(15)

y <- x1 + x2^2 + rnorm(15)
model <- glm(y ~ x1 + I(x2^2))

sectionview3d(model)

if (requireNamespace("DiceEval")) { library(DiceEval)

X = matrix(runif(15*2),ncol=2)
y = apply(X,1,branin)

model <- modelFit(X, y, type = "StepLinear")

sectionview3d(model)

}

## A 2D example - Branin-Hoo function
sectionview3d(branin, col='black')

## Not run:
## a 16-points factorial design, and the corresponding response
d <- 2; n <- 16
design.fact <- expand.grid(seq(0, 1, length = 4), seq(0, 1, length = 4))
design.fact <- data.frame(design.fact); names(design.fact) <- c("x1", "x2")
y <- branin(design.fact); names(y) <- "y"

if (requireNamespace("DiceKriging")) { library(DiceKriging)
## model: km
model <- DiceKriging::km(design = design.fact, response = y)
sectionview3d(model)
sectionview3d(branin, col='red', add=TRUE)
}

if (requireNamespace("rlikkriging")) { library(rlikkriging)
## model: Kriging
model <- Kriging(X = as.matrix(design.fact), y = as.matrix(y), kernel="matern3_2")
sectionview3d(model)
sectionview3d(branin, col='red', add=TRUE)
}

## model: glm
model <- glm(y ~ 1+ x1 + x2 + I(x1^2) + I(x2^2) + x1*x2, data=cbind(y,design.fact))
sectionview3d(model)
sectionview3d(branin, col='red', add=TRUE)

if (requireNamespace("DiceEval")) { library(DiceEval)
## model: StepLinear
model <- modelFit(design.fact, y, type = "StepLinear")
sectionview3d(model)
sectionview3d(branin, col='red', add=TRUE)
}

```

```
## End(Not run)
```

Vectorize.function	<i>Vectorize a multidimensional Function</i>
--------------------	--

Description

Vectorize a d-dimensional (input) function, in the same way that `base::Vectorize` for 1-dimensional functions.

Usage

```
Vectorize.function(fun, dim, .combine = rbind, .lapply = safe_mclapply, ...)
```

Arguments

<code>fun</code>	'dim'-dimensional function to Vectorize
<code>dim</code>	dimension of input arguments of <code>fun</code>
<code>.combine</code>	how to combine results (default using <code>c(.)</code>)
<code>.lapply</code>	how to vectorize FUN call (default is <code>parallel::mclapply</code>)
<code>...</code>	optional args to pass to ' <code>Apply.function()</code> ', including <code>.combine</code> , <code>.lapply</code> , or optional args passed to ' <code>fun</code> '.

Value

a vectorized function (to be called on matrix argument, on each row)

Examples

```
f = function(x)x[1]+1; f(1:10); F = Vectorize.function(f,1);
F(1:10); #F = Vectorize(f); F(1:10);

f2 = function(x)x[1]+x[2]; f2(1:10); F2 = Vectorize.function(f2,2);
F2(cbind(1:10,11:20));

f3 = function(x)list(mean=x[1]+x[2],se=x[1]*x[2]); f3(1:10); F3 = Vectorize.function(f3,2);
F3(cbind(1:10,11:20));
```

Index

Apply.function, [2](#)
are_in.mesh, [3](#)

branin, [4](#)

combn.design, [4](#)
contourview (contourview.function), [5](#)
contourview,character,character-method
 (contourview.function), [5](#)
contourview,function,function-method
 (contourview.function), [5](#)
contourview,glm,glm-method
 (contourview.function), [5](#)
contourview,km,km-method
 (contourview.function), [5](#)
contourview,Kriging,Kriging-method
 (contourview.function), [5](#)
contourview,list,list-method
 (contourview.function), [5](#)
contourview,matrix,matrix-method
 (contourview.function), [5](#)
contourview,WarpKriging,WarpKriging-method
 (contourview.function), [5](#)
contourview.character
 (contourview.function), [5](#)
contourview.function, [5](#)
contourview.glm (contourview.function),
 [5](#)
contourview.km (contourview.function), [5](#)
contourview.Kriging
 (contourview.function), [5](#)
contourview.list
 (contourview.function), [5](#)
contourview.matrix, [10](#)
contourview.matrix
 (contourview.function), [5](#)
contourview.WarpKriging
 (contourview.function), [5](#)

EvalInterval.function, [13](#)

expand.grids, [13](#)

filledcontourview
 (filledcontourview.function),
 [14](#)
filledcontourview,function,function-method
 (filledcontourview.function),
 [14](#)
filledcontourview,glm,glm-method
 (filledcontourview.function),
 [14](#)
filledcontourview,km,km-method
 (filledcontourview.function),
 [14](#)
filledcontourview,Kriging,Kriging-method
 (filledcontourview.function),
 [14](#)
filledcontourview,list,list-method
 (filledcontourview.function),
 [14](#)
filledcontourview,WarpKriging,WarpKriging-method
 (filledcontourview.function),
 [14](#)
filledcontourview.function, [14](#)
filledcontourview.glm
 (filledcontourview.function),
 [14](#)
filledcontourview.km
 (filledcontourview.function),
 [14](#)
filledcontourview.Kriging
 (filledcontourview.function),
 [14](#)
filledcontourview.list
 (filledcontourview.function),
 [14](#)
filledcontourview.WarpKriging
 (filledcontourview.function),
 [14](#)

- is.mesh, 21
- is_in.mesh, 22
- is_in.p, 22
- load3d, 23
- Memoize.function, 23
- mesh, 24
- mesh_exsets, 25
- mesh_level, 26
- min_dist, 27
- min_dist.mesh, 27
- optim.stop, 28
- optims, 29
- parview(parview.function), 30
- parview.function, 30
- plot2d_mesh, 35
- plot3d_mesh, 36
- plot_mesh, 34
- points_in.mesh, 37
- points_out.mesh, 38
- root, 38
- roots, 40
- roots_mesh, 41
- safe_mclapply, 29, 43
- sectionview(sectionview.function), 43
- sectionview,character,character-method
(sectionview.function), 43
- sectionview,function,function-method
(sectionview.function), 43
- sectionview,glm,glm-method
(sectionview.function), 43
- sectionview,km,km-method
(sectionview.function), 43
- sectionview,Kriging,Kriging-method
(sectionview.function), 43
- sectionview,list,list-method
(sectionview.function), 43
- sectionview,matrix,matrix-method
(sectionview.function), 43
- sectionview,WarpKriging,WarpKriging-method
(sectionview.function), 43
- sectionview.character
(sectionview.function), 43
- sectionview.function, 10, 19, 33, 43, 48, 56
- sectionview.glm, 10, 19, 33, 48, 56
- sectionview.glm(sectionview.function),
43
- sectionview.km, 10, 19, 33, 48, 56
- sectionview.km(sectionview.function),
43
- sectionview.Kriging, 10, 19, 33, 48, 56
- sectionview.Kriging
(sectionview.function), 43
- sectionview.list, 33
- sectionview.list
(sectionview.function), 43
- sectionview.matrix, 10, 33, 48, 56
- sectionview.matrix
(sectionview.function), 43
- sectionview.WarpKriging, 10, 19, 33, 56
- sectionview.WarpKriging
(sectionview.function), 43
- sectionview3d(sectionview3d.function),
51
- sectionview3d,character,character-method
(sectionview3d.function), 51
- sectionview3d,function,function-method
(sectionview3d.function), 51
- sectionview3d,glm,glm-method
(sectionview3d.function), 51
- sectionview3d,km,km-method
(sectionview3d.function), 51
- sectionview3d,Kriging,Kriging-method
(sectionview3d.function), 51
- sectionview3d,list,list-method
(sectionview3d.function), 51
- sectionview3d,matrix,matrix-method
(sectionview3d.function), 51
- sectionview3d,WarpKriging,WarpKriging-method
(sectionview3d.function), 51
- sectionview3d.character
(sectionview3d.function), 51
- sectionview3d.function, 10, 19, 48, 51, 56
- sectionview3d.glm, 10, 19, 48, 56
- sectionview3d.glm
(sectionview3d.function), 51
- sectionview3d.km, 10, 19, 48, 56
- sectionview3d.km
(sectionview3d.function), 51
- sectionview3d.Kriging, 10, 19, 48, 56
- sectionview3d.Kriging
(sectionview3d.function), 51
- sectionview3d.list

- (sectionview3d.function), [51](#)
- sectionview3d.matrix, [10](#), [48](#), [56](#)
- sectionview3d.matrix
 - (sectionview3d.function), [51](#)
- sectionview3d.WarpKriging, [10](#), [19](#), [48](#), [56](#)
- sectionview3d.WarpKriging
 - (sectionview3d.function), [51](#)
- Vectorize.function, [59](#)